



**J. Helmke & Co.**  
 Garvensstraße 5  
**D - 30519 Hannover**  
 Tel. +49 (0) 511 / 87 03-0  
 Fax +49 (0) 511 / 86 39 30  
 e-mail: helmke@helmke.de  
 Internet: <http://www.helmke.de>

## Three-Phase Slipring Motors High-Voltage Type DSVK

The Helmke motor series provide reliability and safety.

Slipring motors		Conventional applications
Power:	500 - 12,000 kW	refiners   crushers   mills   fans   shredders
Speed:	3,000 - 250 rpm	
Voltage:	3,000 - 11,000 V	
Degree of protection:	IP 23	
Cooling method:	IC 01 / 81 W	
Frame type:	B3	

### Helmke DSVK modular series

- extremely robust, torsionally stiff, welded housing construction
- winding design for stator and rotor winding in temperature class F (VPI), resistant to humidity, chemically aggressive atmospheres, contamination, tropicalized and vacuum switch resistant
- modular basic construction
- adaptation of cooling through modification of cooler module
- basic construction with continuous, solid shafts (not hollow shaft)  
range as .pdf document
- slipring compartment separated from internal stator chamber in terms of ventilation with brushes in permanent contact – separately ventilated
- two-channel ventilation system with intensive cooling of winding ends



Example:  
 Type DSVK 630-12-037  
 1,400 kW | 6.3 kV  
 500 rpm | IP 23

